



Inbouwmaten (mm)			
DN	15	20	25
	1/2"	3/4"	1"
Geflensd L1	230	230	230
Laseinde L2	160	160	160
H	120	120	120

**Aansluitingen:**

Geflensd DIN of ANSI

Laseinde SW of BW

Draad BSP of NPT

Drukbereik : 0 - 80 bar

Omschrijving	Materiaal			Bestelnummer
	DIN	DIN vergelijkbaar met: ASME		
1 Onderhuis	15 Mo 3	1.5415	A 182 F 1	1701
2 Deksel	15 Mo 3	1.5415	A 182 F 1	1702
3 Zitting	X 10 Cr Ni S 188	1.4305	A 182 F 303	1705
4 Klep (gehard)	X 90 Cr Mo V 18	1.4112	A 182 F 440B	1706
5 Bimetaal schijven	RGR	RGR	RGR	1707
6 Dekselpakking	Grafiet	Grafiet	Grafiet	1716
7 Zittingpakking	Koper	Koper	Koper	1715
8 Filter	X 5 Cr Ni 1810	1.4301	A 182 F 304	1711
9 Bouten	42CrMo4	1.7225	ASTM A320 Gr.L7	1714
10 Moeren	24CrMo5	1.7258	A 194 GR 4	1712
11 Zeskant moer	X 5 Cr Ni 1810	A2-70	A 182 F 304	1708
12 Opvulringetjes	X 5 Cr Ni 1810	1.4301	A 182 F 304	1727